




A brand of  
Aqseptence Group

## Noggerath® Vortex Grit Classifier GCC-V

The removal of sand and mineral solids from wastewater to prevent sedimentation in downstream processes in municipal or industrial sewage treatment plants.



With 20 years of operational experience, the Noggerath® Vortex Grit Classifiers GCC-V have established themselves as a tried and tested solution for the removal of grit and other settleable solids in wastewater treatment processes. Sedimentation is effectively prevented in pump

stations, channels and aeration tanks. Downstream equipment is consistently protected from abrasion. Furthermore, efficient grit removal optimizes the process in biological treatment. The tangential inflow area creates a spiral flow in the tank. A paddle system to improve hy-

draulic efficiency, also ensures uniformly high grit separation, even with varying inflow capacities.

After a full rotation the sewage flows into the outlet channel above the inlet channel. The paddle system is installed vertically in the tank and operates radially, creating a vertical moving spiral flow (vortex) in the center of the tank. The lighter organic matter is thereby lifted and directed back into the stream of wastewater. Heavy mineral matter settles in the center of the tank, dropping into the grit collection shaft, and is transported from there, by means of a grit pump or air-lift pump, for further processing.

The construction of the concrete tank is generally built locally by the general contractor with stainless steel internal parts being provided by Aqseptence Group.

---

### Benefits

- Compact construction due to low space requirement
- Low investment and operating costs
- Easy installation
- High operational reliability
- Low and easy maintenance
- High grit capture rate
- Retrofit capability in existing plants

---

### Unique features

- No controls are necessary
- Total enclosure is possible to reduce offensive odors
- Low control requirements
- Robust, durable stainless steel components

## Design sizes & performance

Type	Diameter (m)	Flow rate (m <sup>3</sup> /h)	Circular Grit Classifier
<b>GCC-V 20</b>	2,0	240	$d\tau \geq 0.30 \text{ mm}$ $\eta = 95 \%$
<b>GCC-V 25</b>	2,5	650	$d\tau \geq 0.21 \text{ mm}$ $\eta = 85 \%$
<b>GCC-V 30</b>	3,0	1.050	$d\tau \geq 0.15 \text{ mm}$ $\eta = 65 \%$
<b>GCC-V 35</b>	3,5	1.600	$d\tau$ = sand particle diameter $\eta$ = separation efficiency (capture rate)
<b>GCC-V 42</b>	4,2	2.400	
<b>GCC-V 50</b>	5,0	3.300	
<b>GCC-V 60</b>	6,0	7.200	
<b>GCC-V 73</b>	7,3	11.400	

## Materials

<b>Support frame, pipe shaft, parts in contact with medium</b>	stainless steel AISI 304 or AISI 316L Others in request
<b>Drive pinion</b>	PA6G
<b>Ball bearing slewing ring</b>	stainless steel AISI C 1045

## Product variants

- Airlift pump with a quick-acting slide valve and stand (at the end of the pipe)
- Dry-installed pump (in the pump pit with a suction head)

## Options

- Local control system
- Break tank (for air release if operation with air-lift pump)
- Channel covers
- Rotary piston blower
- Fat and grease removal downstream in additional device

## Fields of operation

- Sewage treatment plants, small or medium-sized
- Pumping station
- Existing water treatment plant
- Industrial wastewater treatment plant




Illustration  
Noggerath®  
Vortex Grit  
Classifier GCC-V

## Aqseptence Group GmbH Water Treatment Systems

Ziegeleiweg 2  
31675 Bueckeburg · Germany  
Phone +49 5722 882 0  
Fax +49 5722 882 282  
noggerath@aqseptence.com

[www.aqseptence.com](http://www.aqseptence.com)



Version 1.2

The technical data stated in this brochure are indicative only and have to be determined for each individual case. Reserve technical changes.